



Declaration of Performance



1. Identification code of the product type: **204090-30**
Injection mortar, VMZ 300, Q-101, MOD 4090; 204090-30 , for VMZ anchors, 300 ml

2. Batch / LOT No.: See sticker at the package

3. Purpose: Component of a railing system

Generic type	torque controlled bonded anchor
For use in	cracked and non-cracked concrete, C20/25 - C50/60 (EN 206)
Option	1
Loading	Static or quasi static, seismic, category C1 + C2
Material	Injection mortar
Temperature range (if applicable)	Range I: -40°C to +40°C Range II: -40°C to +80°C Range III: -40°C to 120°C

4. Authorized representative: ./.

5. Manufacturer: Q-railing Europe GmbH & Co.KG
Marie-Curie-Straße 8 – 14
D-46446 Emmerich am Rhein

6. System of assessment and verification of constancy of performance: System 1

7. Harmonised Norm: ETA-04/0092 ETAG 001-5

8. Notified body: **DIBT**
Deutsches Institut für Bautechnik Berlin

9. Declared performance:

Essential characteristics	Design method	Performance	Harmonized Technical Specification
Characteristic resistance for tension	ETAG 001, Annex C CEN/TS 1992-4	C2, C10	ETAG 001
Characteristic resistance for shear	ETAG 001, Annex C CEN/TS 1992-4	C4, C11	
Characteristic resistance for seismic loading	TR 045	C6	
Displacement for serviceability limit state	ETAG 001, Annex C CEN/TS 1992-4	C8, C9, C11	
Characteristic resistance under fire exposure	-	-	

Responsible for creating the declaration of performance is the manufacturer specified in Section 5. Signed on behalf of the manufacturer and the name of the manufacturer:

Sean Bartlett
Head of factory production control
Emmerich am Rhein